Evolution of the RHIC Machine Capability

RHIC performance

Luminosity upgrade using
full energy electron cooling (RHIC II)

Electron Beam Ion Source (EBIS)

BROOKHAVEN
NATIONAL LABORATORY

Thomas Roser
RHIC Detector Workshop
November 13 - 14, 2001

Gold Ion Collisions in RHIC



Design Parameters:
Beam Energy = 100 GeV/u
L_{ave} per IR = 2×10^{26} cm^{-2} sec^{-1}

BROOKHAVEN
NATIONAL LABORATORY

Polarized Proton Collisions in RHIC



BROOKHAVEN
NATIONAL LABORATORY

RHIC performance

- Collisions at RHIC design beam energy (100 GeV/nucl)
- 200 MHz rf system operational
  - 5 ns bunch length and an interaction region with $\sigma \sim 25$ cm
- Luminosity exceeding RHIC design luminosity of 2×10^{26} cm^{-2} s^{-1}
- 40% availability is limiting total integrated luminosity

RHIC bunch profile





BROOKHAVEN NATIONAL LABORATORY

Intra-Beam Scattering (IBS) in RHIC





- Longitudinal emittance growth agrees well with model
- Additional source of transverse emittance growth
- IBS determines RHIC Au performance
- Eventually will need electron cooling (see below)

BROOKHAVEN
NATIONAL LABORATORY

RHIC upgrade opportunities

Possible upgrades for heavy ions:

- Increase luminosity
- Increase atomic number: $Au^{197} \rightarrow U^{238}$ (EBIS)
- Increase c.m. energy: 200 GeV $\rightarrow$ 240 GeV

Possible upgrades for protons:

- Increase luminosity
- Increase c.m. energy: 500 GeV $\rightarrow$ 600 GeV
- Further luminosity upgrade

BROOKHAVEN
NATIONAL LABORATORY

RHIC design luminosity

$$L = \frac{3 f_{rev} \gamma}{2} \frac{N_b N^2}{\varepsilon \beta^*} = 9 \text{ to } 1 \times 10^{26} \text{cm}^{-2}\text{s}^{-1} \text{ over } 10 \text{ hours}$$

$$N_b = 56\,;\; N = 1 \times 10^9 ; \varepsilon = 15 \text{ to } 40\pi\mu\text{m}; \beta^* = 2\text{m}$$





BROOKHAVEN
NATIONAL LABORATORY

RHIC Upgrade Possibilities

- 'Enhanced' luminosity (x4) possible with existing machine:
  - Double the number of bunches to 112
  - Decrease β^* from 2 m to 1m
- Further luminosity upgrades can be achieved by:
  - Decreasing β^* further with modified optics
  - Increasing bunch intensity
  - Decreasing beam emittance
- All options are limited by intra-beam scattering and require beam cooling at full energy!
- Preliminary study on RHIC electron cooling shows that luminosity can be increased ten times.
- Energy upgrade to 120 x 120 GeV/u (Au) or 300 x 300 GeV (protons) possible by replacing the DX magnets. (Present DX magnets have the smallest operational margin)

Electron Cooling at RHIC Storage Energy

- RHIC performance is limited by intra-beam scattering.
- Electron beam cooling at full RHIC energy could eliminate this limitation and even reduce beam emittance further.
- Feasibility supported by study produced by BINP (V. Parkhomchuk et al.)
- Bunched electron beam requirements for 100 GeV/u gold beams:
  E = 54 MeV, $\langle I \rangle \leq 100$ mA, electron beam power: ≤ 5 MW!
- Requires high brightness, high power, energy recovering superconducting linac, almost identical to IR FEL at TJNAF
- Has several applications at BNL: PERL, eRHIC (EIC)
- First linac based, bunched electron beam cooling system used at a collider
- First high p_t electron cooler to avoid recombination of e^- and Au^{79+}

Electron cooling of low energy beams





Transverse beam cooling at the Heidelberg Test Storage Ring (TSR)

BROOKHAVEN NATIONAL LABORATORY

The RHIC Electron Beam Cooler



R&D issues:

High intensity photocathode electron gun

High efficiency energy recovering sc linac with magnetized electron beam

Efficient electron beam transport and debunching/bunching

High precision (10 ppm) solenoid for 30 m cooling section.

BROOKHAVEN NATIONAL LABORATORY

RHIC Luminosity and Emittance with Cooling





BROOKHAVEN
NATIONAL LABORATORY

RHIC beam cooling R&D

Feasibility report completed in April 2001, start design.

R&D items:

- High precision solenoid (10 ppm)
- High brightness photocathode electron gun
- A high-current, low-energy-spread linac

2003:[$2.0M]	Build high brightness cathode gun with required duty cycle
	Start construction of energy recovering SC linac
	Start construction of solenoid prototype
2004:[$2.0M]	Start beam tests with photocathode gun
	Complete solenoid prototype
2005:[$2.0M]	Complete and test energy recovering SC linac

Project: $60M (incl. $6M R&D), Construction: 2005 - 2008

BROOKHAVEN
NATIONAL LABORATORY

Heavy Ion Luminosity Upgrades

	RDM	RDM+	RHIC II
Initial emittance(95%) $\pi\mu m$	15	15	15
Final emittance (95%) $\pi\mu m$	40	40	3
Beta function at IR [m]	2.0	1.0	$1.0 \rightarrow 0.5$
Number of bunches	60	120	120
Bunch population [10^9]	2	2	2
Beam-beam parameter per IR	0.0016	0.0016	0.004
Angular size at IR [μrad]	108	153	95
RMS beam size at IR [μm]	216	150	95
Peak luminosity [10^{26} cm^{-2} s^{-1}]	8	32	83
Average luminosity [10^{26} cm^{-2} s^{-1}]	2	8	70

RDM and RDM+ assume 10 hr stores

RHIC II includes electron beam cooling and assumes 5 hr stores since burn-off is high

BROOKHAVEN
NATIONAL LABORATORY

Proton Luminosity Upgrades

	RHIC Spin	RHIC II	Future Upgrade
Emittance(95%) $\pi\mu m$	20	12	12
Beta function at IR [m]	1	1	0.3
Number of bunches	120	120	360
Bunch population [10^{11}]	2	2	2
Beam-beam parameter per IR	0.007	0.012	0.012
Angular size at IR [μrad]	112	86	157
RMS beam size at IR [μm]	112	86	47
Luminosity [10^{32} cm^{-2} s^{-1}]	2.4	4.0	40.0

RUN2001: Au-Au luminosity: 6×10^{26} cm^{-2} s^{-1} [N-N luminosity ~ 10^{31} cm^{-2} s^{-1}]

RHIC II : Beam-beam tune shift limited for 2 interaction regions

Future Upgrade: Mini-beta quads and more bunches

Will also require major detector upgrades

BROOKHAVEN NATIONAL LABORATORY

EBIS/Linac RHIC Pre-Injector

- Highly successful development of Electron Beam Ion Source (EBIS) at BNL
- Reliable, low maintenance Linac-based pre-injector replacing the Tandem Van de Graaffs
- EBIS allows for the production of high intensity uranium beams
- Ready to start construction



EBIS test stand

BROOKHAVEN
NATIONAL LABORATORY

Results from Test EBIS (½ of RHIC EBIS)



	RHIC Requirements	Achieved
E-beam current	10 A	10 A
E-beam energy	20 keV	20 keV
Yield of pos. charges	5.5×10^{11} (Au, 10 A, 1.5m)	3.2×10^{11} (Au, 8 A, 0.7m)
Pulse length	≤ 40 μs	20 μs
Yield of Au^{33+}	3.4×10^{9}	~ 1.5×10^{9}
Yield of U^{45+}	2.4×10^{9}	

BROOKHAVEN
NATIONAL LABORATORY

Summary

- Full design Au luminosity achieved during RUN2001
- RHIC luminosity upgrades (RHIC II):
  - with existing machine: $\times 4$
  - with full energy electron cooler: $\times 10$ possible
- Further upgrades are possible:
  - Higher energy
  - Increased atomic number
  - Even higher luminosity with shorter bunches spacing and mini-beta interaction regions